

www.benoit.cl



DIPPER-T POZOMETRO



The **dipper-T** water level meter is accurate, reliable, and economical. The **dipper-T** uses the same ergonomically designed reel that is used for the Heron interface meter. The tape on the **dipper-T** conforms to US GGG-T-106E, a guarantee of accuracy. A cascade proof 5/8 in(16mm) dia probe is attached to the tape by a strong flexible link that protects the tape at this vulnerable point. The wetted parts of the probe are stainless steel and Teflon®. The instrument is used to accurately measure the static water level in boreholes, wells, and standpipes and can be used to monitor water level changes during drawdown tests. The **dipper-T** is the basic tool for well drillers, hydrogeologists and any other professional concerned with the study of groundwater.

FEATURES

- **Durable** UV and high impact resistant engineered plastic reel with all stainless steel fittings
- Polyester coated steel frame with a comfortable vinyl grip and "third hand" built in casing hanger lets you hang the unit on the well while you record results
- Large **ergonomic** brake and winding handle
- Water and dust proof encapsulated electronics on a removable front panel
- Full depth stainless steel and Teflon® probe
- Flexible link between the tape and probe
- **Accurate** (complies with US GGG-T-106E standards) medium density polyethylene jacketed tape with stretch proof stainless steel conductors
- The standard tapes are marked in feet and 100th/ft or meters and mm
- The tape lengths are 60ft, 100ft, 150ft and 200ft to 2500ft in steps of 100ft (15m, 30m, 50m, 100m, thereafter in 50m increments). Intermediate lengths are to special order
- Costs less than comparable quality units on the market

Note: 400ft (150m) and longer models use aluminum reels for lightness.

AVAILABLE OPTIONS

Kynar® and Tefzel® jacketed tape

A tough protective nylon carrying bag

Narrow 3/8" diameter stainless steel and Teflon® probe

TEMPERATURE



Do You Need To Measure Ground Water Temperature?

Now you can! With the new temperature option available on the Dipper-T.

Read water temperatures from 0° - 110°C with an accuracy of 0.1°C displayed directly on an LCD mounted on the control panel.
No hand held readouts, cables or complicated charts needed.

DIMENSIONS

Reel Weight	5lbs (2kgs)
Tape per 100ft	1.0lb (.45kgs)
Overall Height	13.5 inch (34 cm)
Width	10 inch (25 cm)
Depth	8 inch (20 cm)

www.benoit.cl

